FRAME MOUNTED ELECTRIC START GENERATOR 5500W

FEATURES

- Single cylinder 4-stroke OHV, air cooled engine.
- Recoil / Electric start.
- 12v 9ah battery included.
- Automatic Voltage Regulator (AVR).
- Low oil sensor.
- Digital 3-in-1 meter (Voltage / Frequency / Time).
- Circuit breaker.

SPECIFICATIONS

MAX. OUTPUT	5500W
CONTINUOUS OUTPUT	5000W
DISPLACEMENT	420cc
HORSE POWER	15HP
RUN TIME AT 50% LOAD	13.5h
OUTLETS	2 x 115V 32A 1 x 230V 32A
FUEL TANK CAPACITY	25L
FREQUENCY	50Hz
LENGTH	700mm
WIDTH	680mm
HEIGHT	680mm
WEIGHT	80kg
FUEL TYPE	PETROL
NOISE LEVEL	72dB(A) @ 7m
STARTING METHOD	ELECTRIC / RECOIL
AVR (AUTOMATIC VOLTAGE REGULATOR)	YES

ABBEY ACCESS LTD - Unit 23, Ynyscedwyn Industrial Estate, Trawsffordd, Ystradgynlais, Swansea, SA9 1DT
TEL: 0845 505 3000 www.fordpowerequipment.co.uk

Ford Motor Company trademarks and trade dress used under license to PULSAR PRODUCTS INC.

Official Licensed Product