










INDUSTRIAL RANGE

GENSET 150 KVA BAUDOIN / GRUPEL

1. MAIN FEATURES

T	Three-phase		Oil
	Baudouin / 6M11G4D0/S		Grupel / 274GB160
	DeepSea / 7320	Hz	50 Hz
	1500 r.p.m.	V	400 V
cos φ	0.8		250 A
Standby Power(ESP)	168 kVA		135 kW
Prime Power (PRP)	152 kVA		122 kW
Continuous Power(COP)	-		-

SOUNDPROOF

Length (L)	3100 mm	
Height (H)	1800 mm	
Width (W)	1185 mm	
Weight	2085 kg	
Daily tank	400 L	
Acoustic pressure level @ 1m	80 ± 2 dB(A)	
Acoustic pressure level @ 7m	72 ± 2 dB(A)	

2. ROOM INSTALLATION

EXHAUST SYSTEM	50 Hz		
	COP	PRP	ESP
Exhaust gas temperature (°C)	-	-	550
Exhaust gas flow (m³/min)	-	21.8	24
Evacuated heat (kW)	-	-	-
Maximum back pressure (kPa)	6		
Exhaust silencer attenuation (dB)	18-25		
Output diameter (mm)	114		

VENTILATION SYSTEMS	50 Hz		
	COP	PRP	ESP
Combustion air flow (m³/min)	-	8.24	8.75
Cooling airflow (m³/min)	304.5		
Maximum load losses (Pa)	50		
Alternator cooling air flow (m³/min)	31.44		

RADIATION	50 Hz		
	COP	PRP	ESP
Engine (kW)	-	-	-
Alternator (kW)	9.73	9.73	10.64



3. ENGINE SPECIFICATIONS

GENERAL SPECIFICATIONS	50Hz
Model	6M11G4D0/S
Emissions (UE/USEPA)	Not applicable / Not applicable
Performance grade	G2
Operating method	4 stroke
Fuel type	Oil
Refrigeration system	Closed water circuit / antifreeze
Aspiration system	Turbo-aftercooled
Injection system	Direct
No. and Cylinder arrangement	6 In-line
Displacement (L)	6.75
Cylinder bore (mm)	105
Cylinder stroke (mm)	130
Compression ratio	18:1
Regulation	Electronic
Rotation speed (r.p.m.)	1500
Piston speed (m/s)	6.5
Gross power COP (kWm)	-
Gross power PRP (kWm)	138
Gross power ESP (kWm)	152
Fan Power (kWm)	- / 6 / 6
Net Power COP (kWm)	-
Net Power PRP (kWm)	131.8
Net Power ESP (kWm)	145.8
BMEP COP (kPa)	-
BMEP PRP (kPa)	1636
BMEP ESP (kPa)	1801



CONSUMPTION	50 Hz	
Fuel consumption	l/h	g/kWh
ESP	36.1	199.3
PRP	32.6	198.7
COP	-	-
75%	24.6	199.3
50%	16.7	202.7
Oil consumption	< 0.2% of fuel consumption	

REFERENCE CONDITIONS	
Temperature (°C)	25
Atmospheric pressure (kPa)	100

CAPACITY (°C)	
Coolant (L)	20
Oil (L)	19

STARTING SYSTEM	
Voltage (V)	12
Power (kW)	4
Battery (Ah)	140

4. ALTERNATOR SPECIFICATIONS

GENERAL SPECIFICATIONS	
Model	274GB160
Phases No.	Three-phase
Protection	IP23
Insulation	H
Temperature rise	H
R.F.I. telephone interference	THF < 2%
R.F.I. Suppression	BS EN 61000-6-2 /6-4,VDE 0875G, VDE 0875N
Coupling	Flexible disks
Support	Single bearing



Wave form distortion with no load	< 1,5%
Wave form distortion with balanced linear load	< 5%
Winding Leads	12
Excitation (standard/optional)	Autoexcitado / PMG
AVR Model (standard/optional)	SX460 / MX341
Voltage Regulation (standard/optional)	± 1 % / ± 0,5 %
Icc (standard/optional)	- / 3In:10s

PF (cos Ø)	Phase	Voltage (V)	Power PRP/ESP (kVA)	Efficiency PRP/ESP (%)	Xd	X'd	X''d
0.8	Three-phase	400	160 / 175	92.4 / 92.4	2.02	0.17	0.12



5. CONTROL PANEL



GENSET	DeepSea 7320
Voltage (F-F / F-N)	● / ●
Current intensity	●
Frequency	●
RMS Values	●
Generator phase sequence	●
Generator earth current [a]	○
No. of registers events	250
Real time clock	●
PIN Protection	●
kWh, kVAr, kVAh, kVArh, cos Ø	●
Synchroscope [i]	-
Nº of available outputs [b]	6
Indication of alarms on LCD	●
Engine run hours	●
Total no. of LED indicators	12
No. of LED alarms	4
Sound signalling alarms	●
Scheduler	●
Fuel level	●

ELECTRICAL NETWORK	DeepSea 7320
Voltage (F-F / F-N)	● / ●
Current [a]	-
Frequency	●
kVA,kW, cos Ø [a]	-
Inversion control between main-group	●

PROTECTIONS AND ALARMS	DeepSea 7320
High / low battery voltage	A
Failure in battery charge alternator	A
Failure to stop	A/S
Failure to start	A/S
Low fuel level	A/S
Overload	A/S
Earth leakage	A/S
Asymmetry between phases	A/S
Maintenance	A/S
High / Low generator frequency	A/S
Engine overspeed	A/S
Engine underspeed	A/S
Generator overvoltage	A/S
Generator undervoltage	A/S
ECU Alert (if applicable)	A/S
Low oil pressure	A/S
Low level of radiator water [f]	A/S
Engine high temperature	A/S
Fuel leakage/ theft	A



6. CONTROL PANEL

ENGINE	DeepSea 7320	APPLICATIONS	DeepSea 7320
Engine speed	●	Automatic or manual starting	●
Low oil pressure protection	●	Remote start by NO dry contact	●
Oil pressure reading [c]	○	Automatic by mains failure	●
High temperature engine protection	●	Alternating with timesharing	●
Engine temperature reading [c]	○	Multi-generators synchronization and load sharing (Max. 32 generators)	-
Engine battery voltage	●	Generator-Main in synchronism and load sharing (1 generator and 1 main)	-
Intensity of the engine battery [d]	○		
Fuel Consumption [e]	●		
Low level of radiator water [f]	○		
Engine maintenance scheduled	●		
COMMUNICATION	DeepSea 7320	OPTIONAL EXPANSIONS	DeepSea 7320
USB female type B plug (max. 6m)	●	DSE2130 (8 dig. inputs)	○
USB female type A plug	-	DSE2157 (8 relay outputs)	○
RS232 port (max. 15m)	●	DSE890 (4G LTE and GPS)	○
RS485 port (max. 1,2Km)	●	DSE891 (ethernet module)	○
Ethernet port RJ45 [g/h/i]	○	DSE892 (ethernet module according SNMP protocol)	○
4G LTE + GPS [g]	○	DSE2548 (expansion with 8 additional LEDs)	○
ModBus RTU protocol	●	DSE7320 (mirror controller, maximum distance 1km)	○
ModBus TCP protocol [g/h/i]	○	DSE331 (convert QTC into QTA)	○
SNMP protocol [i]	○	DSE335 (convert QTC into QTA)	○
CAN port (max. 40m)	●		
MSC port (max. 240m)	-		
PLC functionality	●		
Legenda		STANDARDS	
● Available		Working temperature	-30 ≤ °C ≤ 70
○ Optional		Protection index (when assembled with sealing gasket)	IP65 - Quando montado com junta de vedação
- Not available		Degree of humidity (during 48hr)	93%, 40°C durante 48h
A Warning Alarm			
S Stop alarm			
[a] Need additional CT			
[b] No. of outputs available for standard configuration. The outputs do not include relays and additional terminal connections.			
[c] If the information is not provided by the engine-ECU, you need an additional sensor			
[d] Needs additional ammeter			
[e] If information provided by the engine ECU			
[f] Required additional sensor			
[g] Requires DSE890			
[h] Requires DSE891			
[i] Requires DSE892			

Dimensions and guiding weights. Environmental reference conditions: 100kPa, 25 °C, 30% relative humidity and fuel temperature below 40 °C. Power ratings according to ISO 8528-1:2018.

Emergency power (ESP): Maximum power available to supply variable loads for a maximum period of 200h/year. The average load factor in 24h of operation must not exceed 70% of the ESP regime. It does not allow overload.

Prime power (PRP): Maximum power available to supply variable loads for an unlimited number of hours. The average load factor in 24 hours of operation must not exceed 70% of the PRP rating. Allows an overload of 10% for a maximum period of 1 hour every 12 hours of operation. Overloading may not exceed 25 hours/year.

Continuous power (COP): Maximum power available to supply constant loads for an unlimited number of hours per year, between the maintenance intervals and environmental conditions advertised by the manufacturer.

These specifications are subject to change without notice.

DISTRIBUTOR