

The Poly Mobile Tank ranges have been designed for the safe & secure storage and transfer of fuels & fluids.



POLY MOBILE TANKS & ACCESSORIES



Enhanced Design Features

Unique Design Standard

Polyplastic tanks have a double-walled construction with an interstitial space between the walls. This provides an added layer of protection against leaks or spills, making them suitable for hazardous or environmentally sensitive materials.

Dispensing & Accessibility

The Polyplastic tanks allow for easy access for maintenance, refilling, and dispensing. Consider factors like proximity to equipment or machinery that will be using the stored material.

Maintenance & Environment

The manufacturing process for polyplastic tanks often requires less energy compared to producing tanks from materials like steel or concrete. This contributes to reduced energy consumption and environmental impact.

Transportable & Portable

The Polyplastic tanks are designed to be easily moved or transported to different locations as needed. They are constructed with features that facilitate safe and efficient transportation.



POLY MOBILE

D210

Model (PMD-210L)

The Polymobile Diesel 210L polyplastic fuel storage tank has been designed specifically for the storage transport & transfer of fuels with its onboard dispensing equipment.



Specifications

Metric

Model	PMD210L
Capacity	200L
Safe Fuel Fill Level	175L
Length	1100 mm
Width	800 mm
Height	450 mm
Weight	35kg
Flow Rate	40LPM/10.6GPM
Loading Capacity	60 Sets Per one 20ft container

Accessories :

- ✓ 12V Diesel electric pump.
- ✓ Filling cap with padlock availability.
- ✓ High quality auto-shut off nozzle.
- ✓ 4m 3/4" delivery hose with swivel fittings.
- ✓ 4m electric cable.
- ✓ Air Breath.
- ✓ 30 min duty cycle, 30 min on/off.

POLY MOBILE

DF350/55

Model (PMDF-350/55L)

The PMDF-350/55L Poly Mobile Dual Fluid storage tank has been designed specifically for the storage transport and transfer of fuel and fluids, facilitated by its onboard dispensing equipment.



Specifications

Metric

Model	PMDF-350/55L
Capacity	350L Diesel/55L DEF/AdBlue
Safe Fuel Fill Level	300L Diesel/45L DEF/AdBlue
Length	1150 mm
Width	800 mm
Height	690 mm
Weight	63.5kg
Flow Rate	40LPM/10.6GPM(Diesel) & 17LPM/4.5GPM(AdBlue)
Loading Capacity	84 Sets per one 40HC container

Accessories :

- ✓ 12V Diesel electric pump.
- ✓ Filling cap with padlock availability.
- ✓ High quality auto-shut off nozzle.
- ✓ 4m 3/4" delivery hose with swivel and crimped fittings.
- ✓ 4m power cable with crocodile clips.
- ✓ Air Breath.
- ✓ 30 min duty cycle, 30 min on/off.

POLY MOBILE

D400

Model (PMD-400L)

The Polymobile Diesel 400L polyplastic fuel storage tank has been designed specifically for the storage transport & transfer of fuels with its onboard dispensing equipment.



Specifications

Metric

Model	PMD400L
Capacity	400L
Safe Fuel Fill Level	380L
Length	1150 mm
Width	800 mm
Height	680 mm
Weight	53kg
Flow Rate	40LPM/10.6GPM
Loading Capacity	84 Sets per one 40HC container

Accessories :

- ✓ 12V Diesel electric pump.
- ✓ Filling cap with padlock availability.
- ✓ High quality auto-shut off nozzle.
- ✓ 4m 3/4" delivery hose with swivel and crimped fittings.
- ✓ 4m power cable with crocodile clips.
- ✓ Air Breath.
- ✓ 30 min duty cycle, 30 min on/off.

POLY MOBILE

D400HR

Model (PMD-400HR)

The Polymobile Diesel D400HR polyplastic fuel storage tank has been designed specifically for the storage transport & transfer of fuels with its onboard dispensing equipment.



Specifications

Metric

Model	PMD400HR
Capacity	400L
Safe Fuel Fill Level	380L
Length	1150 mm
Width	800 mm
Height	690 mm
Weight	74kg
Flow Rate	56LPM
Loading Capacity	42 Sets Per one 20HC container

Accessories :

- ✓ 12V diesel pump or 230V pump.
- ✓ Auto-shut off nozzle.
- ✓ Level gauge.
- ✓ 10m 3/4" hose reel.
- ✓ 4m electric cable locked.
- ✓ Air Breath.
- ✓ 30 min duty cycle, 30 min on/off.

POLY MOBILE

D980HR

Model (PMD-980HR)

The Polymobile Diesel D980HR polyplastic fuel storage tank has been designed specifically for the storage transport & transfer of fuels with its onboard dispensing equipment.



Specifications

Metric

Model	PMD980HR
Capacity	1000L
Safe Fuel Fill Level	950L
Length	1100 mm
Width	1300 mm
Height	1200 mm
Weight	120kg
Flow Rate	56LPM
Loading Capacity	36 sets per one 40HC container

Accessories :

- ✓ 12V Diesel Pump.
- ✓ Automatic nozzle.
- ✓ Level gauge.
- ✓ LED light.
- ✓ 10m 3/4" hose reel.
- ✓ 4m electric cable Locked.
- ✓ Air Breath.
- ✓ Oil-water separator.
- ✓ 30 min duty cycle, 30 min on/off.

POLY MOBILE

CAB75

Model (PMABCAB-75L)

The Polymobile AdBlue CAB-75L storage tank has been designed with the singular purpose of facilitating the transportation of AdBlue oil.



Specifications

Metric

Model	PMABCAB-75L
Capacity	75L
Safe Fuel Fill Level	65L
Length	450 mm
Width	530 mm
Height	1050 mm
Weight	15kg
Flow Rate	GP10012 10LPM/2.6GPM
Loading Capacity	230 Sets per one 40HQ container

Accessories :

- ✓ Open flow.
- ✓ Diaphragm pump.
- ✓ AD 14PP automatic nozzle with 15mm spot out 5-10LPM.
- ✓ 4m 3/4" delivery hose with swivel and crimped fittings.

POLY MOBILE

AB100

Model (PMAB-100L)

The Polymobile AdBlue 100L storage tank has been designed with the singular purpose of facilitating the transportation of AdBlue oil.



Specifications

Metric

Model	PMAB100L
Capacity	100L
Safe Fuel Fill Level	90L
Length	800 mm
Width	757 mm
Height	450 mm
Weight	23kg
Flow Rate	17LPM/4.5GPM
Loading Capacity	190 Sets per one 40HQ container

Accessories :

- ✓ 12V Self-priming diaphragm pump.
- ✓ Open flow.
- ✓ Pad lockable filling cap.
- ✓ High quality auto-shut nozzle AD 11PP.
- ✓ 4m 3/4" delivery hose.
- ✓ 4m electric cable.

POLY MOBILE

AB200

Model (PMAB-200L)

The Polymobile AdBlue 200L storage tank has been designed with the singular purpose of facilitating the transportation of AdBlue oil.



Specifications

Metric

Model	PMAB200L
Capacity	200L
Safe Fuel Fill Level	180L
Length	1100 mm
Width	640 mm
Height	610 mm
Weight	27kg
Flow Rate	23LPM/6.8GPM
Loading Capacity	120 Sets per one 40HQ container

Accessories :

- ✓ 12V Self-priming diaphragm pump.
- ✓ Open flow.
- ✓ High quality manual nozzle.
- ✓ 4m 3/4" delivery hose.
- ✓ 4m electric cable.
- ✓ 30 min duty cycle, 30 min on/off.

POLY MOBILE

AB210

Model (PMAB-210L)

The Polymobile AdBlue 210L storage tank has been designed with the singular purpose of facilitating the transportation of AdBlue oil.



Specifications

Metric

Model	PMAB210L
Capacity	200L
Safe Fuel Fill Level	180L
Length	1100 mm
Width	640 mm
Height	610 mm
Weight	35kg
Flow Rate	23LPM/6.8GPM
Loading Capacity	150 Sets per one 40HQ container

Accessories :

- ✓ 12V Self-priming diaphragm pump.
- ✓ Open flow
- ✓ High quality manual nozzle.
- ✓ 4m 3/4" delivery hose.
- ✓ 4m electric cable.
- ✓ 30 min duty cycle, 30 min on/of.

POLY MOBILE

AB400

Model (PMAB-400L)

The Polymobile AdBlue 400L storage tank has been designed with the singular purpose of facilitating the transportation of AdBlue oil.



Specifications

Metric

Model	PMAB400L
Capacity	400L
Safe Fuel Fill Level	380L
Length	1100 mm
Width	640 mm
Height	610 mm
Weight	49kg
Flow Rate	23LPM/6.8GPM
Loading Capacity	42 Sets per one 20HC container

Accessories :

- ✓ 12V Self-priming diaphragm pump.
- ✓ High quality manual nozzle.
- ✓ 4m 3/4" delivery hose.
- ✓ 4m electric cable.
- ✓ 30 min duty cycle, 30 min on/off.
- ✓ Air Breath.

POLY MOBILE

AB500

Model (PMAB-500L)

The Polymobile AdBlue 500L storage tank has been designed with the singular purpose of facilitating the transportation of AdBlue oil.



Specifications

Metric

Model	PMAB500L
Capacity	500L
Safe Fuel Fill Level	470L
Length	1720 mm
Width	760 mm
Height	760 mm
Weight	46kg
Flow Rate	23LPM/6.8GPM
Loading Capacity	57 Sets per one 40HQ container

Accessories :

- ✓ 12V Self-priming diaphragm pump.
- ✓ Open flow.
- ✓ High quality auto plastic nozzle.
- ✓ 4m 3/4" delivery hose.
- ✓ 4m electric cable.
- ✓ 30 min duty cycle, 30 min on/off.

POLY MOBILE

AB1000

Model (PMAB-1000L)

The Polymobile AdBlue 1000L storage tank has been designed with the singular purpose of facilitating the transportation of AdBlue oil.



Specifications

Metric

Model	PMAB1000L
Capacity	1000L
Safe Fuel Fill Level	950L
Length	1100 mm
Width	1300 mm
Height	1200 mm
Weight	120kg
Flow Rate	32LPM
Loading Capacity	36 sets per one 40HC container

Accessories :

- ✓ 12V AdBlue Pump.
- ✓ Automatic nozzle.
- ✓ LED light.
- ✓ 6m 3/4" hose EPDM.
- ✓ 4m electric cable Locked.
- ✓ Air Breath.
- ✓ 30 min duty cycle, 30 min on/off.

POLY MOBILE

AB1000HR

Model (PMAB-1000HR)

The Polymobile AdBlue 1000HR storage tank has been designed with the singular purpose of facilitating the transportation of AdBlue oil.



Specifications

Metric

Model	PMAB1000HR
Capacity	1000L
Safe Fuel Fill Level	950L
Length	1100 mm
Width	1300 mm
Height	1200 mm
Weight	120kg
Flow Rate	32LPM
Loading Capacity	36 sets per one 40HC container

Accessories :

- ✓ 12V AdBlue Pump.
- ✓ Automatic nozzle.
- ✓ LED light.
- ✓ 6m 3/4" hose reel.
- ✓ 4m electric cable Locked.
- ✓ Air Breath.
- ✓ 30 min duty cycle, 30 min on/off.



Fuelling Your Progress

DYMAC GLOBAL LTD.

E: sales@dymacglobal.com
T: +353 1 442 0516
BROWNSTOWN ROAD
COMMONS, NEWCASTLE
CO. DUBLIN
IRELAND
D22 Y2F2

DYMAC UK

E: sales@dymacuk.com
T: +44 300 303 3353
SNARESTONE ROAD
NEWTON BURGOLAND
LEICESTERSHIRE
UNITED KINGDOM
LE67 2SN

DYMAC INDIA ENGINEERING PVT LTD.

E: india@dymacglobal.com
T: +91 7349274812
2-18-1557/19,20,21,
AJANTA BUSINESS CENTRE
BEJAI KAPIKAD, MANGALORE
DAKSHINA KANNADA-575004
KARNATAKA, INDIA

DYMAC CANADA INC

E: sales@dymaccanada.com
T: +1 905 564 3654
444 SEAMAN STREET
STONE CREEK
HAMILTON
CANADA
ON L8E 2V9

DYMAC USA INC

E: sales@dymactanks.com
T: +1-240-583-1240
3028 GREENMOUNT AVE #2038
BALTIMORE, MD
UNITED STATES
21218