



STANDBY RANGE

110kVA / 88kW 400V THREE PHASE

Noise Level:

70dB(A) at 7m in free field conditions.

Emissions Class:

Non-Emissions Certified

Connection Type:

Hard-Wired

Typical Application:

Standby duty, permanent installation, commercial & industrial applications



**WATER
COOLED**



**3
PHASE**



**50HZ
400V**



**DIESEL
FUEL**

GENERATOR SET RATING

Output rating	Prime	Standby
50HZ 400/230V, 1500RPM	100kVA	110kVA
	80kW	88kW

ENGINE TECHNICAL DATA

Engine make:	Cummins
Engine model:	6BT5.9-G2
Governing type:	ELEC
Number of cylinders:	6
Cylinders arrangement:	In-line
Bore and stroke:	102 x 120
Displacement:	5.9 (L)
Aspiration:	Turbocharged
Cycle:	4-Stroke
Compression ratio:	17.3:1
Cooling system:	Water Cooled
Frequency & engine speed:	50HZ & 1500RPM

	Prime	Standby
Gross engine power	86kW	-
Fuel consumption @ 100% L/hr	22.3	-
Fuel consumption @ 50% L/hr	-	-

ALTERNATOR DATA

Make:	Depco
Model:	DPC274C
No. of Bearings	1
Insulation Class	H
Ingress protection	IP23
Excitation system	Shunt
Voltage	±1%

DIMENSIONS

Length (mm):	2790
Width (mm):	1100
Height (mm):	1600
Weight* Kg:	1842
Fuel tank capacity:	215 litres

CONTROL PANEL

Make:	Deepsea
Model:	DSE6120

All details subject to change – please confirm before ordering

RATINGS DEFINITION

Prime Power

this rating is applicable for supplying continuous power (at variable load average 70%) in lieu of commercially purchased power. A 10% overload is available for 1 hour in any 12-hour continuous operation

Standby Power

this rating is applicable for supplying continuous power (at variable load) in the even of a utility power failure. No overload if permitted.

STANDARD CONDITIONS

The rating and power outputs are at the standard reference conditions of 27C air inlet temperature, barometric pressure 100kpa and relative humidity of 30%.

The unit will operate at much higher temperatures and pressures but a derate will apply.

AVAILABLE OPTIONS

Coolant Heater

to ensure fast start and load acceptance

Battery Charger

to keep the starter battery in a charged condition.

Three Way Valves

Three Way Valves – for easy connection of an external tank.

Control Panel Upgrades

Control Panel Upgrades – BMS monitoring, remote monitoring, synchronizing.

External Tank Option

External Tank Options – any size supplied and installed.

Ultra Low Noise Level Canopies

Ultra Low Noise Level Canopies – special canopy or container options for sensitive applications.

Automatic Transfer Switches

Automatic Transfer Switches – for starting and transferring the load when the mains power is lost.

Alternator Auxiliary Winding (arep)

for motor starting applications.

WARRANTY



This generator is covered under warranty for 12 months or 1000 hours whichever occurs first. Extended warranty may be available – please ask us for more details.

STANDARD SPECIFICATION

Engine

Heavy Duty, four stroke, water cooled diesel engine running at 1500rpm

Fuel System

Engine driven fuel injector pump with full flow filters (water separator optional)

Cooling System

Water cooled with engine driven fan. Fully guarded and designed to cool at high ambient temperatures.

Exhaust System

Heavy duty residential grade silencer installed within the canopy. Lagged to prevent heat pick-up.

Output Circuit Breaker

Delixi Brand output MCCB, fixed type, 3 pole.

Anti-vibration Mount

Engine and alternator are mounted on AVM's to provide damping of vibrations into the ground.

Coupling

The engine and alternator are close-coupled with a SAE semi-flexible flange.

Safety Guards

The cooling fan drive and moving parts are guarded to prevent personal injury.

Fuel Tank

a large capacity fuel tank is included within the base tank with filler cap, breather, fuel feed and drain lines.

Alternator

Single bearing with class H insulation. All windings are impregnated with a triple dip thermosetting liquid polyester varnish or vacuum pressure coated polyester resin.

Automatic Voltage Regulator (AVR)

Fully sealed automatic voltage regulator maintains the voltage regulation at +-1%