



STANDBY RANGE

750kVA / 600kW 400V 3-PHASE

Noise Level:

72dB(A) at 7m in free field conditions

Emissions Class:

Non-emissions certified

Connection Type:

Hard-Wired – optional sockets available

Typical Application:

Standby duty, permanent installation, commercial & private residences



**WATER
COOLED**



3-PHASE



**50HZ
400V**



**DIESEL
FUEL**

GENERATING SET MODEL

Output rating	Prime	Standby
50HZ 400V, 1500RPM	750kVA	825kVA
	600kW	660kW

ENGINE TECHNICAL DATA

Engine make:	Cummins
Engine model:	KTA38-G2
Governing type:	Electronic
Number of cylinders:	12
Cylinders arrangement:	V-line
Bore and stroke:	159 x 159
Displacement:	38
Aspiration:	Turbo
Cycle:	4-Stroke
Compression ratio:	14.5 : 1
Cooling system:	Water Cooled 50HZ
Frequency & engine speed:	& 1500RPM

Prime Standby

Gross engine power	664kW	-
Fuel consumption @ 100% L/hr	169	-
Fuel consumption @ 50% L/hr	-	-

ALTERNATOR DATA

Make:	Stamford
Model:	S6L1D-C4
No. of Bearings:	1
Insulation Class:	H
Ingress Protection:	IP23
Excitation System:	Shunt
Voltage:	±1%

DIMENSIONS

Length (mm):	5600
Width (mm):	2200
Height (mm):	2520
Weight* Kg:	8900
Fuel tank capacity:	8 Hours

CONTROL PANEL

Make:	Deepsea
Model:	DSE6120

RATINGS DEFINITION

Prime Power

This rating is applicable for supplying continuous power (at variable load average 70%) in lieu of commercially purchased power. A 10% overload is available for 1 hour in any 12-hour continuous operation.

Standby Power

This rating is applicable for supplying continuous power (at variable load) in the event of a utility power failure. No

STANDARD CONDITIONS

The rating and power outputs are at the standard reference conditions of 27C air inlet temperature, barometric pressure 100kpa and relative humidity of 30%.

The unit will operate at much higher temperatures and pressures but a derate will apply.

AVAILABLE OPTIONS

Coolant Heater

To ensure fast start and load acceptance

Battery Charger

To keep the starting battery in charged condition.

Three Way Valves

Three Way Valves – for easy connection of an external tank.

Control Panel Upgrades

Control Panel Upgrades – BMS monitoring, remote monitoring, synchronizing.

External Tank Option

External Tank Options – any size supplied and installed.

Ultra Low Noise Level Canopies

Ultra Low Noise Level Canopies – special canopy or container options for sensitive applications.

Automatic Transfer Switches

Automatic Transfer Switches – for starting and transferring the load when the mains power is lost.

Alternator Auxiliary Winding (arep)

For motor starting applications.

WARRANTY



This generator is covered under warranty for 12 months or 1000 hours whichever occurs first. Extended warranty may be available – please ask us for more details.

STANDARD SPECIFICATION

Engine

Heavy Duty, four stroke, water cooled diesel engine running at 1500rpm

Fuel System

Engine driven fuel injector pump with full flow filters (water separator optional)

Cooling System Water

cooled with engine driven fan. Fully guarded and designed to cool at high ambient temperatures.

Exhaust System

Heavy duty residential grade silencer installed within the canopy. Lagged to prevent heat pick-up.

Output Circuit Breaker

Delixi Brand output MCCB, fixed type, 3 pole.

Anti-vibration Mount

Engine and alternator are mounted on AVM's to provide damping of vibrations into the ground.

Coupling

The engine and alternator are close-coupled with a SAE semi-flexible flange.

Safety Guards

The cooling fan drive and moving parts are guarded to prevent personal injury.

Fuel Tank

A large capacity fuel tank is included within the base tank with filler cap, breather, fuel feed and drain lines.

Alternator

Single bearing with class H insulation. All windings are impregnated with a triple dip thermosetting liquid polyester varnish or vacuum pressure coated polyester resin.

Automatic Voltage Regulator (AVR)

Fully sealed automatic voltage regulator maintains the voltage regulation at +/-1%